

OUTLINE

7490XDI-78 UPLIGHT LOW

CCT (K): 4000
Delivered Lumens (lm): 3005
System wattage (W)*: 22.9
Distribution: Indirect
Delivered Efficacy (lm/W): 131
Photometric type C

Luminous dimensions
Luminous shape: Rectangle
Units: in (mm)
0-180 Axis: 3.9 (100)
90-270 Axis: 78.7 (2000)
Height: 0.0 (0)

7490XDI-78 UPLIGHT REG

CCT (K): 4000
Delivered Lumens (lm): 5862
System wattage (W)*: 47.5
Distribution: Indirect
Delivered Efficacy (lm/W): 123
Photometric type C




Luminous dimensions
Luminous shape: Rectangle
Units: in (mm)
0-180 Axis: 3.9 (100)
90-270 Axis: 78.7 (2000)
Height: 0.0 (0)

7490XDI-78 UPLIGHT HO

CCT (K): 4000
Delivered Lumens (lm): 8552
System wattage (W)*: 74.5
Distribution: Indirect
Delivered Efficacy (lm/W): 115
Photometric type C

Luminous dimensions
Luminous shape: Rectangle
Units: in (mm)
0-180 Axis: 3.9 (100)
90-270 Axis: 78.7 (2000)
Height: 0.0 (0)

*System wattage include driver and LED module consumption



This photometric report has been generated using methods recommended by the IESNA. Calculations are based on simulated photometric data and can change without notice. End-user environment and application (including, but not limited to, voltage variation and dirt accumulation) can cause actual photometric performance to differ from the performance calculated using the data provided by the manufacturer. In no event will Eureka Lighting be responsible for any loss resulting from any use of this report.