

PHOTOMETRIC REPORT

ARENA-AIM
LIGHT SOURCE FOR ARENA 8200

8292-LED-40-NA-BLKE

CCT (K): 4000
Delivered Lumens (lm): 656
DC Load (W): 7.2
Distribution: Direct
Delivered Efficacy (lm/W): 91
Photometric type: C

*System efficacy (lm/W) including driver is 73

Luminous dimensions

Luminous shape: Circular
Units: in (mm)
0-180 Axis: 0 (0)
90-270 Axis: 1.18 (30)
Height: 0 (0)

Luminaire spacing criteria

2 luminaires, plane 0: 0.34
2 luminaires, plane 90: 0.34
2 luminaires, diagonal: 0.34

8292-LED-40-WI-BLKE

CCT (K): 4000
Delivered Lumens (lm): 654
DC Load (W): 7.2
Distribution: Direct
Delivered Efficacy (lm/W): 91
Photometric type: C




*System efficacy (lm/W) including driver is 73

Luminous dimensions

Luminous shape: Circular
Units: in (mm)
0-180 Axis: 0 (0)
90-270 Axis: 1.18 (30)
Height: 0 (0)

Luminaire spacing criteria

2 luminaires, plane 0: 0.52
2 luminaires, plane 90: 0.52
2 luminaires, diagonal: 0.52



This photometric report has been generated using methods recommended by the IESNA. Calculations are based on simulated photometric data and can change without notice. End-user environment and application (including, but not limited to, voltage variation and dirt accumulation) can cause actual photometric performance to differ from the performance calculated using the data provided by the manufacturer. In no event will Eureka Lighting be responsible for any loss resulting from any use of this report.