



4277-DI-25-SGF-LED.LOW.HO

CCT (K): 4000  
Direct delivered Lumens (lm)\*: 1004  
Indirect delivered Lumens (lm): 1525  
System wattage (W)\*: 34.1  
Distribution: Direct and Indirect  
Delivered Efficacy (lm/W): 74  
Photometric type C

Luminous dimensions  
Luminous shape: Rectangle  
Units: in (mm)  
0-180 Axis: 15.7 (400)  
90-270 Axis: 15.7 (400)  
Height: 35.4 (900)

Luminaire spacing criteria  
2 luminaires, plane 0: 1.13  
2 luminaires, plane 90: 1.13  
4 luminaires: 1.21

\*For Silvergray version. Expect a 10% decrease in performance for charcoal, red and navy blue (direct).  
\*Photometric report generated with a 25" Mill.  
Expect no differences with a 14" or 35" Mill.  
\*\*System wattage include driver and LED module consumption



This photometric report has been generated using methods recommended by the IESNA. Calculations are based on simulated photometric data and can change without notice. End-user environment and application (including, but not limited to, voltage variation and dirt accumulation) can cause actual photometric performance to differ from the performance calculated using the data provided by the manufacturer. In no event will Eureka Lighting be responsible for any loss resulting from any use of this report.