

SCOUT BELL PENDANT 4048/4049-BEL

PROJECT PROJÉT

SPEC TYPE

NOTES



FINISH

BLKE

WHE

AYE

BRE

CBE

CPE

DBE

GGE

CHM

SIM

HGE

LNE

NBE

SBE

SGE

STE

MOUNTING OPTIONS OPTIONS DE MONTAGE

4048-BEL-6

4048-BEL-10

4048-BEL-18

4049-BEL-6

4049-BEL-10

4049-BEL-18

ORDERING SPECIFICATION		SPÉCIFICATION DE COMMANDE		CODE	
MODEL MODÈLE					
4048-BEL-6	SCOUT Ø2.75 - 6"				
4048-BEL-10	SCOUT Ø2.75 - 10"				
4048-BEL-18	SCOUT Ø2.75 - 18"				
4049-BEL-6	SCOUT Ø4.5 - 6"				
4049-BEL-10	SCOUT Ø4.5 - 10"				
4049-BEL-18	SCOUT Ø4.5 - 18"				
LIGHT SOURCE		SOURCE LUMINEUSE			
LED	REGULAR OUTPUT				
LED.HO	HIGH OUTPUT				
COLOR TEMPERATURE		TEMPÉRATURE DE COULEUR			
27	2700K				
30	3000K				
35	3500K				
40*	4000K				
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE					
COLOR RENDERING INDEX (CRI)		INDICE DE RENDU DE COULEUR (IRC)		90	
90	90+ CRI				
VOLTAGE		VOLTAGE			
120V	120 VOLT				
277V	277 VOLT				
CONTROL OPTION		OPTION DE CONTRÔLE			
DP*	PHASE DIMMING (120V ONLY)				
DV	0-10V DIMMING (120V-277V)				
NLTAIR2*	NLIGHT AIR CONTROL GEN 2				
NLIGHT*	NLIGHT WIRED CONTROL				
* REQUIRES RC2 CANOPY					
* FOR EMERGENCY BATTERY WITH NLIGHT OPTIONS,PLEASE CONTACT YOUR EUREKA REPRESENTATIVE					
REFER TO NLIGHT GUIDE AND INSTALLATION SHEET FOR ALL REQUIREMENTS.					
EMERGENCY BATTERY		BATTERIE D'URGENCE			
EM DRIVER BOX INCLUDED, INSTALLED REMOTELY. SEE EM GUIDE FOR DETAILS.					
EMB*	EMERGENCY BATTERY FOR REMOTE BOX				
* 3981E ACCESSORY IS REQUIRED FOR THIS OPTION					
STEM OR CABLE		TIGE OU CABLE			
S10*	3/8" (10MM) STEM, NOT FIELD ADJUSTABLE				
C*	BLACK OR WHITE CABLE, FIELD ADJUSTABLE				
C2**	AIRCRAFT SUSPENSION WITH BLACK OR WHITE CABLE, FIELD ADJUSTABLE				
* FOR 4048-FLA CONFIGURATIONS ONLY					
** FOR 4049-FLA CONFIGURATIONS ONLY					
STEM OR CABLE LENGTH		LONGUEUR DE TIGE OU CABLE			
36	36" CABLE (STD LENGTH)				
60	60" CABLE (STD LENGTH)				
**	CUSTOM CABLE OR STEM LENGTH (PLEASE SPECIFY)				
FOR OVERALL LENGTH, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE					
MOUNTING		MONTAGE			
ROUND CANOPY / PAVILLON ROND					
RC1*	SCREWLESS 0.5" CANOPY (2471C)				
RC2	NLIGHT SCREWLESS CANOPY Y Ø7.75" X 1.30" (2474H)				
* 3983 ACCESSORY PROVIDED FOR 4048-BEL-6 AND 4049-BEL-6 WITH 2471C CANOPY					
CANOPY FINISH		FINI PAVILLON			
BLKE	BLACK FINE TEXTURE				
WHE	WHITE FINE TEXTURE				
MATCH*	COLOR MATCH WITH TUBE				
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE					
POWER CORD OR STEM FINISH		FINI CABLE D'ALIMENTATION OU TIGE			
BLK	BLACK POWER CORD				
WH	WHITE POWER CORD				
BLKE	BLACK STEM				
WHE	WHITE STEM				
MATCH*	COLOR MATCH STEM WITH TUBE				
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE					
TUBE FINISH		FINI TUBE			
BLKE	BLACK	CBE*	CHOCOLATE BROWN	NBE*	NAVY BLUE
WHE	WHITE	CPE*	CLAY PINK	SBE*	SAND BEIGE
CHM*	CHAMPAGNE METALLIC	DBE*	DYNAMIC BLUE	SGE*	SAGE GREY
SIM*	SILVER METALLIC	GGE*	GRASS GREEN	STE*	SUMMER TEAL
AYE*	APRICOT YELLOW	HGE*	HUNTER GREEN		
BRE*	BRICK RED	LNE*	LUNAR GREY		
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE					
ACCESSORY		ACCESSOIRE			
3983	DEEP JUNCTION BOX (PROVIDED FOR 4048-BEL-6 AND 4049-BEL-6 WITH CANOPY)				
ACCESSORY EMERGENCY BATTERY		ACCESSOIRE BATTERIE D'URGENCE			
3981EA	ELECTRICAL BOX FOR EMB EMERGENCY BATTERY				

SCOUT - FINISH OPTIONS / OPTIONS DE FINIS Standard



BLKE
Black Textured



WHE
White Textured

Metallic



CHM
Champagne



SIM
Silver


Premium



AYE
Apricot
Yellow
Textured



BRE
Brick Red
Textured




CBE
Chocolate
Brown
Textured



CPE
Clay Pink
Textured



DBE
Dynamic Blue
Textured



GGE
Grass Green
Textured



HGE
Hunter Green
Textured



LNE
Lunar Gray
Textured



NBE
Navy Blue
Textured



SBE
Sand Beige
Textured



SGE
Sage Gray
Textured



STE
Summer Teal
Textured

SCOUT BELL PENDANT 4048/4049-BEL

3 MOUNTING OPTIONS
Pendant version designed with a single black or white cable, easy install and adjust on site. Thin and discreet magnetic canopy. Also available as ceiling mount.

6 FORMATS & 16 FINISHES
Machined aluminum cylindrical structure, offered in a variety of 16 new finishes.

2 DIMMING TYPE
Standard phase dimming (DP) or 0-10V dimming (DV).
Integrated LED driver (404X-DIS-10 & 404X-DIS-18).
Deep junction box (3983) included (404X-DIS-6).

2 OUTPUTS & 4 CCTs
Extruded aluminum heatsink designed to efficiently offer regular and high output.

BELL DIFFUSER
A translucent cloche-shaped shade for a smooth minimalist look.

4048-6 4049-6 4048-10 4049-10 4048-18 4049-18

6.25" 159mm 10.5" 267mm 18" 457mm

Ø2.75" Ø70mm Ø4.5" Ø114mm Ø2.75" Ø70mm Ø4.5" Ø114mm Ø2.75" Ø70mm Ø4.5" Ø114mm

SCOUT EXTRA - ACCESSORY FAMILY

ORB 404X-ORB


PEBBLE 404X-PEB

BELL 404X-BEL

FLARE 404X-FLA

PRODUCT SPECIFICATIONX	X48-XX		XX48-XXX		X49-XX		XX49-XXX		X49-XX	
PERFORMANCE	REG	HO	REG	HO	REG	HO	REG	HO	REG	HO
SYSTEM WATTAGE	9.5W	13.6W	9.5W	13.6W	13.7W	20W	13.7W	20W	13.7W	20W
DELIVERED LUMENS (4000K)	1051 LM	1425 LM	1051 LM	1425 LM	1394 LM	1907 LM	1509 LM	2070 LM	1472 LM	2021LM
EFFICACY	110.6LM/W	104.7LM/W	110.6LM/W	104.7LM/W	101.7LM/W	95.4LM/W	110.1M/W	103.5LM/W	107.4M/W	101LM/W
OTHER INFORMATIONS										
BEAM ANGLE	24°		45°		28°		48°		64°	
LUMINAIRE'S WEIGHT	1.44KG / 163KG / 196KG		1.44KG / 163KG / 196KG		1.87KG / 2.24KG / 275KG		1.87KG / 2.24KG / 275KG		1.87KG / 2.24KG / 275KG	
L70 (LUMEN MAINTENANCE)	3.16LBS/ 3.58LBS/ 4.32LBS		3.16LBS/ 3.58LBS/ 4.32LBS		4.12LBS/ 4.92LBS/ 6.05LBS		4.12LBS/ 4.92LBS/ 6.05LBS		4.12LBS/ 4.92LBS/ 6.05LBS	
	> 63 600 HRS		> 63 600 HRS		> 63 600 HRS		> 63 600 HRS		> 63 600 HRS	

EFFICACY MULTIPLIERS		
CRI	CCT	FACTOR
90+	4000K	1.00
90+	3500K	0.98
90+	3000K	0.94
90+	2700K	0.91





Visit our website for warranty terms and conditions.