

ATOLL - 3850 - WALL

PROJECT PROJÉT
SPEC TYPE
NOTES



FINISH FINI



BLKE

WHE

FAMILY FAMILLE



WALL 3850

CEILING 3850

PENDANT 4850




WALL ACOUSTIC 3851

CEILING ACOUSTIC 3851

PENDANT ACOUSTIC 4851

DRIVER OPTION OPTION DE PILOTE



ORDERING SPECIFICATION SPÉCIFICATION DE COMMANDE

CODE

MODEL MODÈLE

3850-24	ATOLL SURFACE 24"
3850-36	ATOLL SURFACE 36"
3850-48	ATOLL SURFACE 48"
3850-60	ATOLL SURFACE 60"
3850-72	ATOLL SURFACE 72"

LIGHT SOURCE SOURCE LUMINEUSE

LED	REGULAR OUTPUT
LED.HO	HIGH OUTPUT

COLOR TEMPERATURE TEMPÉRATURE DE COULEUR

27	2700K
30	3000K
35	3500K
40*	4000K

*LONGER LEAD TIME MAY APPLY. PLEASE CONTACT YOUR EUREKA REPRESENTATIVE

COLOR RENDERING INDEX (CRI) INDICE DE RENDU DE COULEUR (IRC)

90	90+ CRI	90
----	---------	----

VOLTAGE VOLTAGE

120V	120 VOLT
277V	277 VOLT

CONTROL OPTION OPTION DE CONTRÔLE

DV	0-10V DIMMING (120V-277V)
DP*	PHASE DIMMING (120V ONLY)
NLTAIR2**	NLIGHT AIR CONTROL GEN 2
NLIGHT**	NLIGHT WIRED CONTROL

*ONLY AVAILABLE REGULAR OUTPUT
 **NLIGHT INTEGRATION REQUIRES THE USAGE OF A REMOTE POWER PACK
 **NLIGHT AIR IS NOT AVAILABLE WITH RMP
 **LONGER LEAD TIME MAY APPLY. PLEASE CONTACT YOUR EUREKA REPRESENTATIVE
 REFER TO NLIGHT GUIDE AND INSTALLATION SHEET FOR ALL REQUIREMENTS

EMERGENCY BATTERY BATTERIE D'URGENCE

EM DRIVER BOX INCLUDED. INSTALLED REMOTELY. SEE EM GUIDE FOR DETAILS

EMB*	EMERGENCY BATTERY FOR REMOTE BOX
------	----------------------------------

*3981EA ACCESSORY IS REQUIRED

DRIVER POSITION POSITION DU PILOTE

RDP	RECESSED DRIVER (3981C)
	NOT AVAILABLE FOR 3850-36/48/60/72-HO OR 3850-72-REG
RMP	REMOTE DRIVER (3981GC)

CANOPY FINISH FINI PAVILLON

BLKE	BLACK FINE TEXTURE
WHE	WHITE FINE TEXTURE
RAL*	PLEASE SPECIFY RAL CODE

*LONGER LEAD TIME MAY APPLY. PLEASE CONTACT YOUR EUREKA REPRESENTATIVE

RING FINISH FINI ANNEAU

BLKE	BLACK FINE TEXTURE
WHE	WHITE FINE TEXTURE
RAL*	PLEASE SPECIFY RAL CODE

*LONGER LEAD TIME MAY APPLY. PLEASE CONTACT YOUR EUREKA REPRESENTATIVE

ACCESSORY ACCESSOIRE

3981C	JUNCTION BOX FOR RECESSED DRIVER BOX - 2.88" X 3.5" X 6"
3981GC	DRIVER BOX FOR REMOTE INSTALLATION - 3.83" X 12" X 16"
39NLAA	NLIGHT AIR GEN 2 REMOTE CONTROLLER
39NLWA	NLIGHT WIRED REMOTE CONTROLLER

ACCESSORY EMERGENCY BATTERY ACCESSOIRE BATTERIE D'URGENCE

3981EA	ELECTRICAL BOX FOR EMB EMERGENCY BATTERY
--------	--

PRODUCT CHARACTERISTICS CARACTÉRISTIQUES DU PRODUIT



DESIGN:

Atoll is a high-performance ring fixture producing an evenly distributed luminous glow. It comes in 5 different sizes and offers a range of mounting options. The fixture's angled knife-edge diffuser adds a contemporary touch, allowing it to effortlessly fill spaces with simplicity and elegance.

INSTALLATION:

Whether wall or ceiling mounted, Atoll has a simple 3 points mounting system.

LIGHT SOURCE:

Custom designed and manufactured light engine featuring high performance discreet LEDs. Tuneable white and emergency option available.

CONSTRUCTION:

Seamslessly finished, rolled aluminium extrusion profile paired with high efficiency reflectors and a flexible silicone diffuser. Architectural grade matte polyester powder coating outer finish available in white and black.

ATOLL - 3850 - WALL - TUNABLE WHITE

PROJECT PROJÉT
SPEC TYPE
NOTES



FINISH FINI



BLKE

WHE

FAMILY FAMILLE



WALL 3850

CEILING 3850

PENDANT 4850




WALL ACOUSTIC 3851

CEILING ACOUSTIC 3851

PENDANT ACOUSTIC 4851

DRIVER OPTION OPTION DE PILOTE



ORDERING SPECIFICATION	SPÉCIFICATION DE COMMANDE	CODE
MODEL MODÈLE		
3850-24	ATOLL SURFACE 24"	
3850-36	ATOLL SURFACE 36"	
3850-48	ATOLL SURFACE 48"	
3850-60	ATOLL SURFACE 60"	
3850-72	ATOLL SURFACE 72"	
LIGHT SOURCE SOURCE LUMINEUSE		
LED	REGULAR OUTPUT	
LED.HO	HIGH OUTPUT	
COLOR TEMPERATURE TEMPÉRATURE DE COULEUR		TW
TW*	TUNABLE WHITE (2700K TO 5000K) <small>*LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE</small>	
COLOR RENDERING INDEX (CRI) INDICE DE RENDU DE COULEUR (IRC)		80
80	80+ CRI	
VOLTAGE VOLTAGE		
120V	120 VOLT	
277V	277 VOLT	
CONTROL OPTION OPTION DE CONTRÔLE		
DDV	0-10V DIMMING (120V-277V)	
NLT*	NIGHT NTUNE CONTROL <small>*LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE *REFER TO NLIGHT GUIDE AND INSTALLATION SHEET FOR ALL REQUIREMENTS</small>	
DRIVER POSITION POSITION DU PILOTE		RMP
RMP	REMOTE DRIVER (3981GC)	
CANOPY FINISH FINI PAVILLON		
BLKE	BLACK FINE TEXTURE	
WHE	WHITE FINE TEXTURE	
RAL*	PLEASE SPECIFY RAL CODE <small>*LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE</small>	
RING FINISH FINI ANNEAU		
BLKE	BLACK FINE TEXTURE	
WHE	WHITE FINE TEXTURE	
RAL*	PLEASE SPECIFY RAL CODE <small>*LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE</small>	
ACCESSORY ACCESSOIRE		
3981GC	DRIVER BOX FOR REMOTE INSTALLATION - 3.83" X 12" X 16"	

PRODUCT CHARACTERISTICS CARACTÉRISTIQUES DU PRODUIT




- DESIGN:** Atoll is a high-performance ring fixture producing an evenly distributed luminous glow. It comes in 5 different sizes and offers a range of mounting options. The fixture's angled knife-edge diffuser adds a contemporary touch, allowing it to effortlessly fill spaces with simplicity and elegance.
- INSTALLATION:** Whether wall or ceiling mounted, Atoll has a simple 3 points mounting system. Custom designed and manufactured light engine featuring high performance discreet LEDs. Tuneable white and emergency option available.
- CONSTRUCTION:** Seamlessly finished, rolled aluminium extrusion profile paired with high efficiency reflectors and a flexible silicone diffuser. Architectural grade matte polyester powder coating outer finish available in white and black.
- CONCEPTION:** Atoll est un luminaire circulaire haute performance qui produit une illumination uniforme. Disponible en 5 tailles différentes avec une variété d'options de montage, il est doté d'un diffuseur biseauté qui apporte une touche contemporaine et lui permet de remplir les espaces avec simplicité et élégance.
- INSTALLATION:** Que ce soit en suspension ou en surface, Atoll dispose d'un système de montage simple à 3 points.
- SOURCE LUMINEUSE:** Module conçu et fabriqué sur mesure avec des DEL discrets de haute performance. Blanc dynamique ou batterie d'urgence disponible.
- BASE:** Profilé en aluminium extrudé et roulé sans ligne de joint visible, accompagné de réflecteurs à haute efficacité et d'un diffuseur flexible en silicone. Finition extérieure par revêtement de polyester mat de grade architectural disponible en blanc et noir.


ATOLL - 3850 - DIMENSIONS

THICKNESS OF THE RING: 2.75" / 70mm


3850-24
ATOLL 24"




3850-36
ATOLL 36"




3850-48
ATOLL 48"




3850-60
ATOLL 60"



3850-72
ATOLL 72"






PRODUCT SPECIFICATION	3850-24		3850-36		3850-48		3850-60		3850-72	
	REG	HO	REG	HO	REG	HO	REG	HO	REG	HO
PERFORMANCE										
SYSTEM WATTAGE	19.3W	39.6W	28.4W	60.0W	39.0W	79.2W	48.7W	99.6W	56.7W	120.0W
DELIVERED LUMENS - (4000K)	1884LM	3606.9LM	2779LM	5463LM	3811LM	7222LM	4759LM	9066LM	5554LM	10 918LM
EFFICACY	97.6LM/W	91.1LM/W	97.9LM/W	91.1LM/W	97.7LM/W	91.2LM/W	97.7LM/W	91LM/W	98LM/W	91LM/W
OTHER INFORMATION										
WEIGHT OF FIXTURE	6.6LBS / 3KG		10.1LBS / 4.6KG		13.2LBS / 6KG		16.8LBS / 7.6KG		20.3LBS / 9.2KG	
L70 (LUMEN MAINTENANCE)	> 60 000 H		> 60 000 H		> 60 000 H		> 60 000 H		> 60 000 H	

EFFICACY MULTIPLIERS

CRI	CCT	FACTOR	TW FACTOR
80+	5000K	-	0.93
80+	4000K	-	1.00
80+	3500K	-	0.99
80+	3000K	-	0.98
80+	2700K	-	0.91
90+	4000K	1.00	-
90+	3500K	0.96	-
90+	3000K	0.92	-
90+	2700K	0.87	-

LIGHT DISTRIBUTION




Visit our website for warranty terms and conditions.



TECHNICAL DATA

HAUTE PERFORMANCE
Modules sur mesure DEL Nichia option REG et HO avec couleur blanche ajustable (2700K-5000K).




OPTIONS POUR FINITION DES ANNEAUX

Profilé en aluminium robuste, finition en poudre texturée de qualité supérieur disponible en noir ou blanc. Couleurs personnalisées disponibles sur demande.

DIFFUSEUR EN SILICONE

Avec agents anti-jaunissement et une stabilité aux rayons UV. Permet d'avoir une seule ligne de joint discrète pour toutes les grandeurs.





EFFICACITÉ

La lumière des bandes DEL est contrôlée avec des réflecteurs efficaces à 98%. Cela permet à Atoll d'avoir une excellente performance, autant optique qu'énergetique.


MONTAGE SURFACE MINIMALE

Avec une profondeur de 2.9" Atoll est conforme à la norme ADA lorsqu'il est installé au mur.



Atoll est disponible avec une plaque de recouvrement permettant une installation élégante.


OPTIONS DE PILOTES



ENCASTRÉ (RDP)
6.14" x 0.1"
Installation sur boîte 3981C (vendue séparément)
Pilote encastré pour une installation discrète



À DISTANCE (RMP)
6.14" x 0.1"
Installation sur boîte de connexion 4" standard
Pilote dans boîte à distance pour une installation discrète



BOÎTE PILOTES À DISTANCE
12" x 16" x 3.83"


*Se référer à la fiche d'installation RMP pour connaître la distance maximale entre la boîte pilotes à distance et le luminaire

SPÉCIFICATION PRODUIT	3850-24		3850-36		3850-48		3850-60		3850-72	
	REG	HO	REG	HO	REG	HO	REG	HO	REG	HO
PERFORMANCE										
PUISSANCE TOTALE	19.3W	39.6W	28.4W	60.0W	39.0W	79.2W	48.7W	99.6W	56.7W	120.0W
LUMENS RÉELS DIRECT (4000K)	1884LM	3606.9LM	2779LM	5463LM	3811LM	7222LM	4759LM	9066LM	5554LM	10 918LM
EFFICACITÉ	97.6LM/W	91.1LM/W	97.9LM/W	91.1LM/W	97.7LM/W	91.2LM/W	97.7LM/W	91LM/W	98LM/W	91LM/W
AUTRES INFORMATION										
POIDS DU LUMINAIRE	6.6LBS / 3KG		10.1LBS / 4.6KG		13.2LBS / 6KG		16.8LBS / 7.6KG		20.3LBS / 9.2KG	
L70 (MAINTENANCE DE LA LUMIÈRE)	> 60 000 H		> 60 000 H		> 60 000 H		> 60 000 H		> 60 000 H	

FACTEUR D'EFFICACITÉ

CRI	CCT	FACTEUR	FACTEUR TW
80+	5000K	-	0.93
80+	4000K	-	1.00
80+	3500K	-	0.99
80+	3000K	-	0.98
80+	2700K	-	0.91
90+	4000K	1.00	-
90+	3500K	0.96	-
90+	3000K	0.92	-
90+	2700K	0.87	-

DISTRIBUTION LUMINEUSE



DIRECTE



Visitez notre site Web pour les termes et conditions.