




Spin



Fixture #3036

3036-WH-FT5C22

EUREKA

One 22W T5 Circline Compact Fluorescent

Photometric Report

Table with lamp specifications: Number of lamps: 1, Lumens per lamp: 1800.00, Input watts: 25.00, Distribution: Direct-Indirect, Efficiency: 54.6, Photometric type: C, Luminous shape: Rectangle, Units: Feet, Luminous Dimensions: 0-180 Axis: 1.640, 90-270 Axis: 1.640, Height: 0.329, Spacing Criteria (0): 1.25, Spacing Criteria (90): 1.34, Spacing Criteria (Four Luminaires): 1.54


Zonal Lumen Summary table with columns: Zone, Lumens, %Lamp, %Fixt. Rows include zones 0-30, 0-40, 0-60, 0-90, 90-120, 90-150, 90-180 and a total of 982 lumens at 55% efficiency.

Luminance Data table with columns for beam angles (0.0 to 315.0) and rows for distances (0.0 to 85.0). Values represent lumens per square foot at various distances.

Total Luminaire Efficiency = 55%

Coefficients of Utilization

Utilization coefficient table with columns for beam angles (0.80, 0.70, 0.50, 0.30, 0.10, 0.0) and rows for mounting heights (0 to 10 feet). Values range from 30 to 59.



Candela Distribution

Candela distribution table with columns for beam angles (0.0 to 360.0) and rows for distances (0.0 to 180.0). Values represent candela at various distances.